



Revolabs Fusion™ 4 and 8 Wireless Microphone System Product Specifications

Dimensions

Fusion Base Station

- 16.45" (41.8 cm) x 8.46" (21.5 cm) x 3.42" (8.7 cm)

Charger Base

- 8.3" (21.1 cm) x 4.3" (10.9 cm) x 1.0" (2.56 cm)

Radio Frequency

North America

- 1.92 to 1.93 GHz (UPCS North America)

International

- 1.88 to 1.90 GHz (DECT EU)

Connectors

Fusion Base Station

- IR Remote Serial DB9
- CD Programming Serial DB9 for Revolabs use only
- Audio Control RJ45 – for Revolabs use only
- Telephone Line-In RJ11
- Telephone Set-In RJ11
- Network RJ45 – for Revolabs use only
- XLR male
- Aux In RCA Plug
- Aux Out RCA Plug
- Record Out RCA Plug
- Room Out RCA Plug
- Conference In RCA Plug
- Conference Out RCA Plug

Charger Base

- DC power input port
- Proprietary 4 pin microphone charge jacks

Audio Bandwidth

- 100-6800 Hz

Power Requirements

Fusion Base Station

- 100-240V AC, 50-60 Hz, 5W (Universal Inputs)

Charger Base

- 5V DC, 2 Amps (switching power supply varies by country)

Range

- 100' (30 meters) approx. (no obstructions)
- Out-of-range alarm

Channels

- 4 or 8 channels per system

Battery

- Lithium Polymer
- 8 hours talk time

Charge Time

- 2 hours

Encryption

- 128-bit proprietary (per microphone channel)

Environmental Requirements

Temperature

- 40° to 100° F (5° to 40° C) operating

Humidity

- 20% to 85%

Wireless
Flexible
Secure
Rechargeable
Cost-effective
Easy-to-use

Applications:
Tele-conferencing
Video-conferencing



Québec Montréal
Tél. : (418) 681-2470 Tél. : (514) 871-1994

www.presence.qc.ca

Hear Every Word!