

ST30P & ST50P

Active two-way stereo speakers

AT A GLANCE

- > On board stereo power amplifier
- > 30 watt RMS or 50 watt RMS
- > Complete with "U" brackets
- > Stereo RCA inputs
- > Bass, Treble and Volume controls on board
- > Available in black or white
- > Supplied as pairs (one passive, one active)
- > High quality sound reproduction



A MORE THOROUGH EXAMINATION

The AMAV ST30P and ST50P are active two way stereo speaker systems. Supplied in pairs, each ST30P and ST50P consist of one powered and one passive speaker. Both are of a compact and architecturally pleasing design and feature on board stereo amplifier, treble, bass and volume control, power switch, stereo RCA line input and speaker output. The ST30P and ST50P deliver 30 watts and 50 watts respectively.

The new AMAV ST powered speakers deliver high quality sound reinforcement for a variety of audio visual applications. Compact and well-designed, they are easy to operate and will become a standard in many AV installations.

ANNAV

▲ AUSTRALIAN MONITOR AUDIO VISUAL


ST30P & ST50P

Active two way stereo speakers

ARCHITECTURAL SPECIFICATION

The speakers shall be of compact, two-way design with each pair comprising a powered speaker with on board stereo amplifier and a passive speaker.

Onboard controls will be available for volume, bass and treble adjustment and mounting will be via "U" style brackets. The speaker will be powered via mains IEC type connector. RMS power rating will be 30 watts/50 watts RMS. The speakers shall be the AMAV ST30P and AMAV ST50P.



MODEL ST30P	ST30P Passive Speaker	ST30P Active Speaker
WOOFER	Diameter	5.25"
	Impedance	8 ohm
TWEETER	Diameter	0.5" dome
	Impedance	8 ohm
SYSTEM SPECIFICATIONS	Power	30 Watts
	Impedance	8 ohm
	Sensitivity	89dB
	Frequency response	60Hz to 20kHz
POWER AMPLIFIER	Power output	/
	Equalization	/
	Frequency response	/
	AC Power input	/
DIMENSION (h x w x d)	245mm x 183mm x 166mm	245mm x 183mm x 166mm
NET WEIGHT (one each active + passive)	/	6Kgs per pair
Carton	/	500mm x 481mm x 327mm

MODEL ST50P	ST50P Passive Speaker	ST50P Active Speaker
WOOFER	Diameter	6.5"
	Impedance	8 ohm
TWEETER	Diameter	0.8" dome
	Impedance	8 ohm
SYSTEM SPECIFICATIONS	Power	50 Watts
	Impedance	8 ohm
	Sensitivity	89dB
	Frequency response	45Hz to 20kHz
POWER AMPLIFIER	Power output	/
	Equalization	/
	Frequency response	/
	AC Power input	/
DIMENSION (h x w x d)	300mm x 215mm x 190mm	300mm x 215mm x 190mm
NET WEIGHT (one each active + passive)	/	8.9Kgs per pair
Carton	/	561mm x 557mm x 382mm

ENGINEERED AND DISTRIBUTED BY AUDIO TELEX COMMUNICATIONS PTY LTD

ABN 78 001 345 482 Website: www.audiotelex.com.au 1 Clyde Street, Silverwater, Sydney NSW 2128 Australia

For export enquiries email: international@audiotelex.com.au Website: www.australianmonitor.com.au

NSW Phone: (02) 9647 1411 Fax: (02) 9648 3698 VIC Phone: (03) 9890 7477 Fax: (03) 9890 7977 QLD Phone: (07) 3852 1312

WA Phone: (08) 9204 0200 Fax: (08) 9244 3783 SA Phone: (08) 8352 4444 Fax: (08) 8352 4488 NZ Phone: (09) 415 9426

Québec Montréal
Tél. : (418) 681-2470 Tél. : (514) 871-1994

www.presence.qc.ca